



Pegasus

QR Code & Card Reader

Applied with EM card / Mifare card / Felica card / DESFire card / QR code / Barcode



PQ-510

Features

- It can connect off-line and on-line controller.
- Scan the Barcode or QR code to record the access events.
- Built-in buzzer for sound notification.
- Provides tamper switch.
- Ability to read multiple formats.
- With CPU watch-dog function to prevent malfunction.
- Provide OEM/ODM projects development.

Specification

- Frequency : 125KHz ASK /125KHz FSK / 13.56MHz
- Applicable cards : EM 4001,EM 4102 compatible / TEMIC 5557/ Mifare S50, S70, Ultra Light
- Output format (Interface) : RS-232 / RS-485 / Wiegand 26/34bits
- Mounting : Surface Mount
- Power input : DC 12V



Personal access control



Production control



Suite rental management



Meeting attendance



Ordering information

- PQ-510HW : EM & QR Code(Barcode) proximity reader, Wiegand 26&34bits, DC 12V
- PQ-510H2W : EM & QR Code(Barcode) proximity reader, HC(Wiegand 26~37bits,Depending on card), QR code(Wiegand 26&34bits), DC 12V
- PQ-510NR2H02 : EM & QR code Barcode reader,RS232,10H
- PQ-510NR2D01 : EM & QR code Barcode reader,RS232, 8D, carriage return
- PQ-510M0R2H01: Mifare & QR code Barcode reader,RS232,8H,reverse

PONGEE INDUSTRIES CO., LTD.

5F., No.738, Chung-Cheng Rd., Chung-Ho District, New Taipei City 23511, Taiwan

Tel : 886-2-82280198

Fax : 886-2-82280191

E-mail : pongee@pongee.com.tw

Website:http://www.pongee.com

We reserve the right to change the specification without prior notice or obligation!



20201214